

**GENERAL DESCRIPTION:**

Weld-On® PC-64™ is a purple or clear, low VOC emission, non-bodied, solvent primer-conditioner. It is specifically designed to prepare PVC and CPVC plastic pipe and fitting surfaces for bonding with solvent cements.

**APPLICATION:**

WELD-ON PC-64 is suitable for use with all types, classes and schedules of PVC and CPVC pipe and fittings. PC-64 removes grease, oil and dirt from the bonding surfaces of PVC and CPVC pipe and fittings. It also penetrates and softens the pipe and fittings surfaces in preparation for solvent cement application.

**AVAILABILITY:**

WELD-ON PC-64 purple is available in ¼ pint (118 ml), ½ pint (237 ml), pint (473 ml), quart (946 ml) and gallon (3.785 l) metal cans. WELD-ON PC-64 clear is available in quart (946 ml) metal cans only. For detailed information on containers and applicators, see our current Price List.

**STANDARDS AND CERTIFICATION LISTINGS:**

- Meets SCAQMD Rule 1168/316A
- Compliant with LEED® (Leadership in Energy and Environmental Design). When using this WELD-ON low VOC product, credit may be claimed for LEED Green Building Rating System – Indoor Environmental Quality.

**SPECIFICATIONS:**

COLOR: Clear or Purple  
SPECIFIC GRAVITY: 0.814 ± 0.04  
BROOKFIELD VISCOSITY: Water Thin

**SHELF LIFE:**

3 years in tightly sealed containers. The date code of manufacture is stamped on the bottom of the container. Stability of the product is limited by the evaporation of the solvent when the container is opened. Evaporation of solvent will also cause the primer's effectiveness to be reduced. Do not mix new primer or cleaner with partially used or expired primer or cleaner.

**QUALITY ASSURANCE:**

Weld-On PC-64 is carefully evaluated to assure that consistent high quality is maintained. Fourier transform infrared spectroscopy, gas chromatography, and additional in depth testing ensures each batch is manufactured to exacting standards. A batch identification code is stamped on each can and assures traceability of all materials and processes used in manufacturing this product.

**SPECIAL PRECAUTION:**

Weld-On solvent cements must never be used in PVC piping system using or being tested by compressed air or gases; including air-over-water booster. If using in conjunction with flue gas ventilation systems, review the recommendations of the HVAC manufacturer's equipment related to installation and venting. Note that such recommendations may only refer to ASTM standards addressing installation of PVC pipe and fittings, and not to the use of PVC pipe and fittings in flue gas ventilation systems. Also review the technical information available from manufacturers of PVC pipe and fittings concerning the use of their products in flue gas ventilation systems.

Do not use a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system – this solution will be nonvolatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

This product is intended for use by skilled individuals at their own risk. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Detailed directions on making solvent cemented joints are printed on the container label. It is highly recommended that the installer review the instructions supplied by the pipe and fitting manufacturer.

*Refer to the current Weld-On PC-64 Safety Data Sheet for additional safety precautions, first-aid, storage, handling, transportation and disposal information.*



**WARRANTY:**

Weld-On Adhesives, Inc., warrants to all original purchasers of Weld-On products that all new Weld-On products shall be of good quality and free from defects in material and workmanship for the product's shelf life. If any Weld-On product becomes defective, or fails to conform to this written limited warranty under normal use and storage conditions, and if the original purchaser complies with the terms of this limited warranty, then Weld-On will, without charge, replace the nonconforming product.

This limited warranty shall extend to all products manufactured and sold by Weld-On. However, this limited warranty shall not extend to, nor shall Weld-On be responsible for, damages or loss resulting from accident, misuse, negligent use, improper application, or incorporation of Weld-On products into other products. In addition, any repackaging of Weld-On products also shall void the limited warranty provided herein.

Any defective Weld-On products shall be replaced pursuant to the terms of this limited warranty by returning the defective product, with transportation charges prepaid, to Weld-On at the following address:

Weld-On Adhesives, Inc.  
Attn: Customer Service  
455 West Victoria Street  
Compton, CA 90220

Any implied warranty in connection with any Weld-On product hereby is limited in duration to the period of this limited warranty. Weld-On shall not be responsible for, nor does this limited warranty extend to, consequential damage, or incidental damage or expense, including without limitation, injury to persons or property or loss of use. This limited warranty is in lieu of all other express warranties of Weld-On, and Weld-On does not assume, nor does it authorize any person to assume on its behalf, any other obligation or liability.