LevelPro[®] — 250L Series Loop Powered Liquid Level Display





Chameleon Color Display Outdoor Visibility Display Automatically Changes from **Blue** to **Green**





LevelPro[®] — 250L Series Loop Powered Liquid Level Display



LevelPro





Chameleon Color Display Outdoor Visibility Display Automatically Changes from **Blue** to **Green**

Specifications

Display	4 Digit Chameleon Color LCD (38mm x 22mm)	
Displayed Values	-999 ± 9999	
Power Supply	Loop Powered	
Protection Class	NEMA 4X IP67	
Accuracy	0.1% @ 25°C One Digit	
Operating Temperature	-20 - 158°F (-29 - 70°C)	
Storage Temperature	-20 - 158°F (-29 - 70°C)	
Protection Class	NEMA 4X IP67	
Case	Wall Mounted Material - Polycarbonate	
Dimensions (WxNxD)	110 x 105 x 67 mm	

Model Selection

ITC250-L — Loop Powered Level Display			
Part Number	Input	Enclosure	
ITC250-L	4-20mA	NEMA 4X	



Features


- O Loop Powered
- ✓ Super Bright 4 Digit LCD Display
- ⊘ Chameleon Color Display
- ⊘ Momentary or Adjustable Relay Timer*
- ⊘ NEMA 4X Enclosure
- ⊘ All Plastic Corrosion Resistant
- ⊘ All Cord Grips Included
- ⊘ Simple Programming

The LevelPro[®] level process displays and controllers are the industry's most rugged and reliable wall-mount remote level displays.

The LevelPro® 250L Series level process display and controller is the industry's most rugged and reliable wall-mount remote level display.

LevelPro® 250L Series comes as a complete all-in-one unit, out of the box it is ready to use. Included is a vivid LCD display, NEMA 4X enclosure, polycarbonate faceplate, cord grips and plastic captive screws.

The industrial design of the 250L Series ensures it will withstand the industry's most corrosive environments.





Wiring Diagram

