

Precision | Durability | Versatility

Measure with Confidence



LevelPro® — TVF-450 Series Industrial Flow Batching Controller

LevelPro®

- ✓ Super Bright LED Display
- ✓ NEMA 4X Enclosure
- ✓ Security Protection



Features

- ✓ Large Bright LED Display
- ✓ 4-20mA + 2 Relay Outputs
- ✓ 6-Digit LED Display
- ✓ Output RS-485 | Modbus RTU
- ✓ Easy to Program

Specifications

Power Supply	Standard : 85 – 260VAC
Input Signal	4-20mA Pulse
Contact	0 2 SPST Relays 4 SPST Relays
Switching Voltage	Max. 250VAC
Switching Current	3AMP
DC Output	24VDC to Sensor
Operating Temp	-40°F - 122°F -40 - 50°C
Display	6-digit LED display
Range of Indication	-99999 – 999999
Accuracy (25°C)	± 0.1 % FSO
Dimensions	96 x 48 x 98 mm
Housing	Panel Mount
Enclosure	NORYL - GFN2S E1

Ordering

Part Number	Input	Output
TVF-450-1121	4-20mA	4 Relay
TVF-450-1122	4-20mA	2 Relay
TVF-450-1129	4-20mA	4-20mA + 2 Relay
TVF-450P-1121	Pulse	4 Relay
TVF-450P-1122	Pulse	2 Relay
TVF-450P-1129	Pulse	4-20mA + 2 Relay

Contact factory for 24VDC option

ENC-100	Enclosure — Wall Mount
---------	------------------------

ENC-100 Wall Mount Enclosure (Optional) + TVF-450 Display

Corrosion Resistant

Lockable

Integral Wall Mount Bracket

Typical Application

