

Kuri Tec®

Series K4131, K4132, K4137 600 PSI PVC Spray Reinforced Hose

NEW!
Performance-Plus
Three Year Warranty!
(See Page 52 for Details)

**LAWN
& PEST
CONTROL
SPRAYING!**



REINFORCED LOW & HIGH PRESSURE SPRAY/TRANSFER HOSES

Excellent quality spray hoses made with premium quality PVC compounds, ideally-suited for lawn and ornamental spray applications using wettable powder chemicals. (Not recommended for high pressure tree spray applications.)

Construction:

- K4131 - Yellow, K4132 - Orange and K4137 - Mint Green.
- Tube — Yellow, Orange, or Mint Green PVC.
- Reinforcement — High tensile strength yarn; one-pass spiral construction.
- Cover — Yellow, Orange, or Mint Green ribbed PVC.

Features:

- Economically priced.
- Ribbed cover for reduced drag and increased flexibility.
- Pin-pricked cover vents vapor . . . helps prevent ballooning.
- Non-marking.

- Light weight — easily coiled after use.
- Longitudinal reinforcing yarns enhance coupling retention and reduce elongation under pressure.
- Chemical resistance of quality PVC for the transfer or spraying of “wetable powder” type chemicals. Not recommended for use with emulsifiable chemicals based on hydrocarbon carriers.
- Silicone-free.
- One-piece lengths.

Applications:

- Lawn spraying.
- Agricultural spraying.
- Vineyard spraying.
- Nursery spraying.
- Building washdown.

Service Temperature Range: +25°F (-5°C) to +150°F (+65°C)

Standard Stock Colors			Size Code	Nominal ID		Nominal OD		Max. Working Pressure† (PSI)		Standard Coil Lengths	Approx. Wt. per Pkg.	
K4131 Yellow	K4132 Orange	K4137 Mint Green		(In)	(mm)	(In)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)		300 ft.	400 ft.
✓	✓	✓	06	3/8	9.5	.625	15.9	600	250	300 or 400 ft.	35 lbs.	46 lbs.
✓	✓	✓	08	1/2	12.7	.790	20.0	600	250	300 or 400 ft.	54 lbs.	72 lbs.

† **Note:** Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Use of hydraulic or reusable-type fittings are not recommended for coupling Kuri Tec® hose products. Hose claims involving use of these fittings will be disallowed.

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.