

Mill Discharge Assemblies

Double Jacket “Contractor Grade” Coupled with Male and Female Aluminum Rocker Lug Couplings

APPLICATIONS:

- Municipal washdown
- Hydrant-to-truck water supply line
- Heavy duty equipment or pump rental
- Ship deck washdown

CONSTRUCTION:

- Double jacket with 100% polyester yarn. Water and mildew-resistant cover, will not rot, even if the hose is stored wet.

FEATURES & BENEFITS:

- Smooth natural rubber tube - Provides strength and flexibility.
- Double Jacket - Provides greater abrasion resistance.
- Wide range of operating temperatures - Hose may be used in temperatures from -25° F (-31° C) to 185° F (+85° C) without stiffening.
- Easy identification - White cover with single blue stripe.
- Packaging/ storage - Individually packed in cartons for ease of handling and shipping. Hose coils easily for storage.



Service Temperature: -25° F (-31° C) to 185° F (+85° C)

Nominal Specifications

Series No.	Size (in.) (mm)	Length (ft.)	Thread Type	Max. Working Pressure (PSI)	Approx. Weight (lbs.)
DJ150NSTX50	1 1/2 38.1	50'	NST	200	12
DJ150NPSHX50	1 1/2 38.1	50'	NPSH	200	12
DJ250NSTX50	2 1/2 63.5	50'	NST	200	23
DJ250NPSHX50	2 1/2 63.5	50'	NPSH	200	23

Note: Not intended for use as a fire hose.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.