

# Redi-Lock® 300

## Non-Conductive 300 PSI Push-On Hose

- **NON-CONDUCTIVE - TESTED TO ONE (1) MEGOHM PER INCH RESISTANCE MINIMUM**
- **MSHA APPROVED FLAME RESISTANT COVER**
- **EASY TO COUPLE**
- **LONG LENGTHS ON REELS**

### APPLICATIONS:

- Low Pressure Pneumatic Systems
- Air Tools
- Water, Oil and Mild Chemical Solutions
- Robotic Welders

★Not recommended for unleaded gasoline

Special colors available in Blue, Gray and Red. Call for availability and or minimum run requirements.

**Cover:** Black Nitrile/PVC

**Reinforcement:** Aramid Spiral Yarn

**Tube:** Nitrile

**Oil Resistance:** RMA - Class A

**Branding:** REDI-LOCK NON-CONDUCTIVE

300 PSI <size> MADE IN USA MSHA1C - 114/03

**Packaging:** MAXIMUM 2 PCS ON REEL

1/4" - 5/8" ID hoses supplied on plastic reels, 3/4" ID hoses supplied on wooden reels

**Note:** For Push-On Fittings and Quick Disconnect Couplings refer to pages 13-15 of this catalog.



**Service Temperature Range:** -30°F (-34°C) to 180°F (+82°C)

### Nominal Specifications

Part Number	Color	ID (in.)	OD (in.)	Working Pressure (PSI)	Reel Length (ft.)	Approx. Weight (lbs/pc)
REDI-LOC-04X700	Black	1/4	1/2	300	700	70
REDI-LOC-06X700	Black	3/8	5/8	300	700	91
REDI-LOC-08X700	Black	1/2	3/4	300	700	112
REDI-LOC-10X700	Black	5/8	29/32	300	700	161
REDI-LOC-12X700	Black	3/4	1 1/32	300	700	182

Note: Cut lengths for this product are available from our Kuriyama Schaumburg, IL Warehouse location. Please call (847) 755-0360 or e-mail: sales@kuriyama.com for more information.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.