



| CODE | ND | D1 | D | Thread | L Thread min | L1 | L2 | L | H1 | H |
|--------------|---------------|------|------|----------|--------------|------|------|------|------|------|
| 27NGM2012NPT | 1/2" => 20 mm | 0.55 | 1.46 | 1/2" NPT | 0.53 | 0.63 | 2.13 | 2.70 | 1.08 | 1.81 |
| 27NGM2512NPT | 3/4" => 25 mm | 0.55 | 1.46 | 1/2" NPT | 0.53 | 0.67 | 2.13 | 2.82 | 1.20 | 1.93 |
| 27NGM2534NPT | 3/4" => 25 mm | 0.73 | 1.65 | 3/4" NPT | 0.55 | 0.67 | 2.13 | 2.89 | 1.20 | 2.03 |
| 27NGM3212NPT | 1" => 32 mm | 0.55 | 1.65 | 1/2" NPT | 0.53 | 0.71 | 2.40 | 3.23 | 1.42 | 2.24 |
| 27NGM3234NPT | 1" => 32 mm | 0.73 | 1.65 | 3/4" NPT | 0.55 | 0.71 | 2.40 | 3.31 | 1.42 | 2.24 |
| 27NGM321NPT | 1" => 32 mm | 0.95 | 2.13 | 1" NPT | 0.68 | 0.79 | 2.56 | 3.41 | 1.85 | 2.91 |

| | | | | |
|--|--|--|-------------------------------|-------------------|
| NIRON® <small>AMERICAS</small> | ITEM: NGM_NPT <small>C:\Vault\Temp\Disegni\Corinal\Tabelle\Niron\POLLO\USA\Ngm_Npt.prt\c1\N10058.dwg</small> | DESC: MALE THREADED 90° ELBOW W/NPT LEAD FREE BRASS - SOCKET FUSION | DRAWING No: NI10058 | |
| | | | SHEET OF 1 | REV. -1 |

www.nupiamericas.com - info@nupiamericas.com

All dimensions have to be considered in inches with 5% tolerance if not otherwise mentioned excluding values as per standard ASTM F2389

All right reserved - Drawing cannot be reproduced in anyway, failure to do so will entitle nupigeco to legal action. Information on this document are subject to change without notice