



CODE	ND	Thread	L Thread min	D1	D	L1	L	CH	LCH
27NRFM2012NPT (A)	1/2" => 20 mm	1/2" NPT	0.53	0.56	1.46	0.63	2.17	-	-
27NRFM2034NPT (A)	1/2" => 20 mm	3/4" NPT	0.55	0.71	1.69	0.81	2.48	-	-
27NRFM2512NPT (A)	3/4" => 25 mm	1/2" NPT	0.53	0.56	1.46	0.67	2.21	-	-
27NRFM2534NPT (A)	3/4" => 25 mm	3/4" NPT	0.55	0.71	1.65	0.69	2.44	-	-
27NRFM3234NPT (A)	1" => 32 mm	3/4" NPT	0.55	0.71	1.79	0.79	2.70	-	-
27NRFM321NPT (A)	1" => 32 mm	1" NPT	0.68	0.95	2.13	0.79	2.80	-	-
27NRFM401NPT (C)	1" 1/4 => 40 mm	1" NPT	0.68	0.95	2.21	0.87	3.39	1.34	0.51
27NRFM40114NPT (B)	1" 1/4 => 40 mm	1"1/4 NPT	0.71	1.30	2.56	0.87	3.58	1.65	0.59
27NRFM50114NPT (C)	1" 1/2 => 50 mm	1"1/4 NPT	0.71	1.30	2.76	0.98	3.66	1.65	0.59
27NRFM50112NPT (B)	1" 1/2 => 50 mm	1"1/2 NPT	0.72	1.50	2.95	0.98	3.68	1.97	0.59
27NRFM63112NPT (C)	2" => 63 mm	1"1/2 NPT	0.72	1.50	3.47	1.14	3.84	1.97	0.59
27NRFM632NPT (B)	2" => 63 mm	2" NPT	0.76	1.95	3.62	1.14	4.13	2.36	0.71
27NRFM752NPT (C)	2" 1/2 => 75 mm	2" NPT	0.76	1.95	4.06	1.30	4.29	2.36	0.71
27NRFM75212NPT (B)	2" 1/2 => 75 mm	2"1/2 NPT	1.14	2.50	4.33	1.30	4.41	3.15	0.79
27NRFM903NPT (B)	3" => 90 mm	3" NPT	1.20	2.95	5.08	1.46	5.08	3.54	0.91
27NRFM1104NPT (B)	4" => 110 mm	4" NPT	1.30	3.92	6.30	1.69	5.83	4.53	1.18
27NRFM1254NPT (C)	5" => 125 mm	4" NPT	1.30	3.92	6.30	1.87	6.00	4.53	1.18

NIRON® 	ITEM: NRFM_NPT	DESC: MALE THREADED ADAPTER W/NPT LEAD FREE BRASS - SOCKET FUSION	DRAWING No: NI10062
			SHEET OF REV. 1 1 -1

C:\Vault\Temp\Disegni\Comuni\Tabella\Niron\POLLO\NI USA\Nrfm_Npt.pptx\NI10062.dwg

www.nupiamericas.com - info@nupiamericas.com All dimensions have to be considered in inches with 5% tolerance if not otherwise mentioned excluding values as per standard ASTM F2389

All right reserved - Drawing cannot be reproduced in anyway, failure to do so will entitle nupigeco to legal action. Information on this document are subject to change without notice