



| CODE | ND | D1 | D2 | D | Thread | L Thread min | L1 | L2 | L | H1 | H |
|------------------|--------------|------|------|------|----------|--------------|------|------|------|------|------|
| 27NTF2012NPT (A) | 1/2 => 20 mm | 0.56 | 1.46 | 1.14 | 1/2" NPT | 0.53 | 0.63 | 1.08 | 2.17 | 1.54 | 2.11 |
| 27NTF2512NPT (A) | 3/4 => 25 mm | 0.56 | 1.46 | 1.38 | 1/2" NPT | 0.53 | 0.67 | 1.20 | 2.40 | 1.54 | 2.22 |
| 27NTF2534NPT (A) | 3/4 => 25 mm | 0.73 | 1.65 | 1.38 | 3/4" NPT | 0.55 | 0.67 | 1.20 | 2.40 | 1.54 | 2.22 |
| 27NTF3212NPT (B) | 1 => 32 mm | 0.56 | 1.65 | 1.65 | 1/2" NPT | 0.53 | 0.79 | 1.48 | 2.95 | 1.61 | 2.44 |
| 27NTF3234NPT (B) | 1 => 32 mm | 0.73 | 1.65 | 1.65 | 3/4" NPT | 0.55 | 0.79 | 1.48 | 2.95 | 1.61 | 2.44 |
| 27NTF321NPT (B) | 1 => 32 mm | 0.95 | 2.13 | 1.65 | 1" NPT | 0.66 | 0.79 | 1.85 | 3.74 | 1.54 | 2.60 |



ITEM: NTF_NPT

DESC: FEMALE THREADED TEE W/NPT LEAD
FREE BRASS - SOCKET FUSION



DRAWING No:

NI10060

SHEET OF

REV.

1 1 -1

www.nupi.americas.com - info@nupi.americas.com

All dimensions have to be considered in inches with 5% tolerance if not otherwise mentioned excluding values as per standard ASTM F2389

All right reserved - Drawing cannot be reproduced in anyway, failure todo so will entitle nupigeco to legal action. Information on this document are subject to change without notice